



# FUYR BEARING CO.,LTD.



1.969 Inch | 50 Millimeter x 3.543 Inch | 90  
Millimeter x 0.787 Inch | 20 Millimeter SKF 7210  
BECBY/W64E Angular Contact Ball Bearings

Bearing No. 7210 BECBY/W64E

7210 BECBY/W64E Bearing 2D drawings and 3D CAD  
models

|                                 |  |
|---------------------------------|--|
| Category                        | Angular Contact Ball Bearings  |
| Inventory                       | 0.0  |
| Manufacturer Name               | SKF  |
| Minimum Buy Quantity            | N/A  |
| Weight                          | 0  |
| Product Group                   | B00308   |
| Enclosure                       | Open   |
| Flush Ground                    | Yes  |
| Rolling Element                 | Ball Bearing   |
| Number of Rows of Balls         | Single Row   |
| Precision Class                 | ABEC 1   ISO P0  |
| Maximum Capacity / Filling Slot | No   |
| Snap Ring                       | No   |
| Cage Material                   | Brass  |
| Contact Angle                   | 40 Degree  |
| Internal Clearance              | CB   |
| Number of Bearings              | 1 (Single)   |
| Mounting Arrangement            | Universal  |
| Inch - Metric                   | Metric   |
| Long Description                | 50MM Bore; 90MM Outside Diameter; 20MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap |



## FUYR BEARING CO.,LTD.

|                        |   |
|------------------------|---|
|                        | Ring; CB; Brass Cage; 40 Degree; 1 (Single); Universa |
| Other Features         | Normal Axial Internal Clearance                       |
| Category               | Angular Contact Ball Bearing                          |
| UNSPSC                 | 31171531  |
| Harmonized Tariff Code | 8482.10.50.28   |
| Noun                   | Bearing   |
| Keyword String         | Angular Contact                                       |
| Manufacturer URL       | <a href="http://www.skf.com">http://www.skf.com</a>   |
| B                      | 0.787 Inch   20 Millimeter                            |
| D                      | 3.543 Inch   90 Millimeter                            |
| d                      | 1.969 Inch   50 Millimeter                            |